

Ball valves

Model 50057 2-part F/F ball valve (58308) with electric actuator IP68 (50840)



Specifications

⇒ Valve

Dimensions: DN8 to DN80 (1/4" to 3")

Connection: BSP female thread

Pressure: PN63 (1000 lbs)

Operating temperature: -29°C to +175°C

Material: 316 or CF8M stainless steel
(for the stainless steel parts that can come into contact with the transported fluid)


⇒ Electric actuator

Operating temperature: -10°C to +55°C

Plastic housing IP68


Visual position indicator

Anti-condensation heater



DN (mm)	NB (inches)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Opening/ closing time (90°) (s)	Weight (kg)	Part No. 100-230V AC and 100-350V DC	Opening/ closing time (90°) (s)	Part No. 15-30V AC and 12-48V DC
8	1/4"	67	195	136	92	11	1.38	450057-8A	11	450057-8B
10	3/8"	67	195	136	92	11	1.35	450057-10A	11	450057-10B
15	1/2"	67	195	136	92	11	1.31	450057-15A	11	450057-15B
20	3/4"	70	201	136	92	12	1.41	450057-20A	12	450057-20B
25	1"	85	210	136	92	12	1.90	450057-25A	12	450057-25B
32	1 1/4"	94	215	136	92	26	2.22	450057-32A1	24	450057-32B1
32	1 1/4"	94	239	151	128	7	3.32	450057-32A2	7	450057-32B2
40	1 1/2"	105	224	136	92	26	2.84	450057-40A1	24	450057-40B1
40	1 1/2"	105	248	151	128	7	3.94	450057-40A2	7	450057-40B2
50	2"	125	255	151	128	12	5.17	450057-50A	12	450057-50B
65	2 1/2"	155	276	151	128	12	7.90	450057-65A	12	450057-65B
80	3"	173	285	151	128	23	15.00	450057-80A	22	450057-80B

Electric actuator with plastic housing with IP68 protection rating.
 Visual position indicator. Manual override control with safe clutch disengagement.
 Configurable limit switches. Torque limiting device. Anti-condensation heater.
 Actuator operating temperature: -10°C to +55°C.
 Duty cycle: 50%. Number of starts per hour: 150.
 Actuator sized for a valve $\Delta P = \max$. 16 bar. For $\Delta P > 16$ bar, please contact us.
 Standard operation: Opening/closing at 0/90°.



N°	Part Name	Material	Quantity
1	2-PART VALVE (58308)	CF8M	1
2	FIXING BOLT	STAINLESS STEEL	4
3	WASHER	STAINLESS STEEL	4
4	COUPLING	STAINLESS STEEL	0 or 1
5	ELECTRIC ACTUATOR (50840)	PLASTIC	1

You can refer to the following product data sheets for more technical information:

- **58308** : 2-part female/female valve
- **50840** : 1/4 turn (90°) electric actuator - IP68

Béné Inox – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – www.bene-inox.com – bene@bene-inox.com

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.