

# Ball valves

## Model 50277 Wafer ball valve with ISO mounting plate (58249) and electric actuator IP66 (50840)



## Specifications

→ Valve

**Dimensions:** DN15 to DN80 (1/2" to 3")

**Connection:** flanges in accordance with EN 1092-1

**Pressure:** PN depending on flange dimensions

**Operating Temperature: -29°C to +175°C**

**Material:** 316 or CF8M stainless steel

(for the stainless steel parts that can come into contact with the transported fluid)

## → Electric actuator

**Operating temperature:** -10°C to +55°C

Plastic housing IP66


## Visual position indicator

## Self-regulating anti-condensation heater



**Béné Inox** – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287  
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – [www.bene-inox.com](http://www.bene-inox.com) – [bene@bene-inox.com](mailto:bene@bene-inox.com)

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.



DN (mm)	NB (inches)	PN (bar)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Opening/ closing time (90°) (s)	Weight (kg)	Part No. 100-230V AC and 100-350V DC	Opening/ closing time (90°) (s)	Part No. 15-30V AC and 12-48V DC
15	1/2"	40	42	194	136	92	11	2.40	450277-15A	11	450277-15B
20	3/4"	40	43	201	136	92	12	2.60	450277-20A	12	450277-20B
25	1"	40	50	211	136	92	12	3.60	450277-25A	12	450277-25B
32	1"1/4	40	60	215	136	92	26	4.50	450277-32A1	24	450277-32B1
32	1"1/4	40	60	239	151	128	7	5.60	450277-32A2	7	450277-32B2
40	1"1/2	40	65	224	136	92	26	5.80	450277-40A1	24	450277-40B1
40	1"1/2	40	65	248	151	128	7	6.90	450277-40A2	7	450277-40B2
50	2"	40	78	254	151	128	12	8.80	450277-50A	12	450277-50B
65	2"1/2	16	110	276	151	128	12	12.20	450277-65A	12	450277-65B
80	3"	16	120	285	151	128	23	16.90	450277-80A	22	450277-80B

Electric actuator with plastic housing with IP66 protection rating.

Visual position indicator. Manual override control with safe clutch disengagement.

Configurable limit switches. Torque limiting device. Anti-condensation heater.

Actuator operating temperature: -10°C to +55°C (except for the fail-safe version: -10°C to +40°C).


Duty cycle: 50%. Number of starts per hour: 150.

Actuator sized for a valve  $\Delta P = \text{max. } 16 \text{ bar}$ . For  $\Delta P > 16 \text{ bar}$ , please contact us.

Standard operation: Opening/closing at 0/90°.

**Béné Inox** – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287  
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – [www.bene-inox.com](http://www.bene-inox.com) – [bene@bene-inox.com](mailto:bene@bene-inox.com)

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.



N°	Part Name	Material	Quantity
1	WAFER VALVE (58249)	CF8M	1
2	FIXING BOLT	STAINLESS STEEL	4
3	WASHER	STAINLESS STEEL	4
4	COUPLING	STAINLESS STEEL	0 or 1
5	ELECTRIC ACTUATOR (50840)	PLASTIC	1

You can refer to the following product data sheets for more technical information:

- **58249** : Wafer valve
- **50840** : ¼ turn (90°) electric actuator - IP66