

Ball valves

Model 50317 2-part ball valve with flanges and ISO mounting plate (58269) and electric actuator IP68 (50840)



Specifications

⇒ Valve

Dimensions: DN15 to DN80 (1/2" to 3")

Connection: flanges in accordance with EN 1092-1

Pressure: PN depending on flange dimensions

Operating Temperature: -29°C to +175°C

Material: 316 or CF8M stainless steel

(for the stainless steel parts that can come into contact with the transported fluid)


⇒ Electric actuator

Operating temperature: -10°C to +55°C

Plastic housing IP68

Visual position indicator

Self-regulating anti-condensation heater



DN (mm)	NB (inches)	PN (bar)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Opening/ closing time (90°) (s)	Weight (kg)	Part No. 100-230V AC and 100-350V DC	Opening/ closing time (90°) (s)	Part No. 15-30V AC and 12-48V DC
15	1/2"	40	115	200	136	92	11	3.45	450317-15A	11	450317-15B
20	3/4"	40	120	205	136	92	12	4.25	450317-20A	12	450317-20B
25	1"	40	125	211	136	92	12	5.10	450317-25A	12	450317-25B
32	1 1/4"	40	130	223	136	92	26	6.70	450317-32A1	24	450317-32B1
32	1 1/4"	40	130	247	151	128	7	7.80	450317-32A2	7	450317-32B2
40	1 1/2"	40	140	228	136	92	26	8.10	450317-40A1	24	450317-40B1
40	1 1/2"	40	140	252	151	128	7	9.20	450317-40A2	7	450317-40B2
50	2"	40	150	261	151	128	12	11.80	450317-50A	12	450317-50B
65	2 1/2"	16	170	278	151	128	23	18.60	450317-65A	22	450317-65B
80	3"	16	180	288	151	128	23	25.40	450317-80A	22	450317-80B

Electric actuator with plastic housing with IP68 protection rating.

Visual position indicator. Manual override control with safe clutch disengagement.

Configurable limit switches. Torque limiting device. Anti-condensation heater.

Actuator operating temperature: -10°C to +55°C (except for the fail-safe version: -10°C to +40°C).

Duty cycle: 50%. Number of starts per hour: 150.


Actuator sized for a valve $\Delta P = \max$. 16 bar. For $\Delta P > 16$ bar, please contact us.

Standard operation: Opening/closing at 0/90°.

Béné Inox – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287

Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – www.bene-inox.com – bene@bene-inox.com

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.



N°	Part Name	Material	Quantity
1	2-PART VALVE WITH FLANGES (58269)	CF8M	1
2	FIXING BOLT	STAINLESS STEEL	4
3	WASHER	STAINLESS STEEL	4
4	COUPLING	STAINLESS STEEL	0 or 1
5	ELECTRIC ACTUATOR (50840)	PLASTIC	1

You can refer to the following product data sheets for more technical information:

- **58269** : 2-part valve with flanges and ISO mounting plate
- **50840** : 1/4 turn (90°) electric actuator - IP68