

# Ball valves

## High pressure 3-way F/F/F ball valve with L-shaped bore and fail-safe electric actuator IP66 (5084I)

**Model 50366** BSP

**Model 50396** NPT



### Specifications

#### ⇒ Valve

**Dimensions:** DN8 to DN25 (1/4" to 1")

**Connection:** BSP or NPT female thread

**Pressure:** 1/4" to 1/2" - PN500  
3/4" to 1" - PN315

**Operating temperature:** -20°C to +100°C

**Material:** 316 stainless steel

(for the stainless steel parts that can come into contact with the transported fluid)


#### ⇒ Electric actuator

**Operating temperature:** -10°C to +40°C

Plastic housing IP66

Visual position indicator

Regulated anti-condensation heater



**100-230V 50/60Hz and 100-350V DC**


DN (mm)	NB (inches)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Opening/ closing time (90°) (s)	Weight (kg)	BSP part number	NPT part number
8	1/4"	69	269	151	128	7	3.21	450366-8A	450396-8A
10	3/8"	72	274	151	128	7	3.41	450366-10A	450396-10A
15	1/2"	83	276	151	128	7	3.71	450366-15A	450396-15A
20	3/4"	95	293	151	128	12	4.31	450366-20A	450396-20A
25	1"	113	301	151	128	23	5.01	450366-25A	450396-25A

**15-30V 50/60Hz and 12-48V DC**

DN (mm)	NB (inches)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Opening/ closing time (90°) (s)	Weight (kg)	BSP part number	NPT part number
8	1/4"	69	269	151	128	7	3.21	450366-8B	450396-8B
10	3/8"	72	274	151	128	7	3.41	450366-10B	450396-10B
15	1/2"	83	276	151	128	7	3.71	450366-15B	450396-15B
20	3/4"	95	293	151	128	12	4.31	450366-20B	450396-20B
25	1"	113	301	151	128	22	5.01	450366-25B	450396-25B

**Béné Inox** – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287  
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – [www.bene-inox.com](http://www.bene-inox.com) – [bene@bene-inox.com](mailto:bene@bene-inox.com)

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.



N°	Part Name	Material	Quantity
1	HP BALL VALVE (58533 or 58535)	316 STAINLESS STEEL	1
2	FIXING BRACKET	STAINLESS STEEL	1
3	SHAFT	STAINLESS STEEL	1
4	COUPLING	STAINLESS STEEL	0 or 1
5	ELECTRIC ACTUATOR (50841)	PLASTIC	1
6	WASHER	STAINLESS STEEL	4
7	FIXING BOLT	STAINLESS STEEL	4
8	FIXING BOLT	STAINLESS STEEL	4
9	WASHER	STAINLESS STEEL	4

You can refer to the following product data sheets for more technical information:

- **58533**: High pressure 3-way ball valve with BSP female threading
- **58535**: High pressure 3-way ball valve with NPT female threading
- **50841**: Fail-safe 1/4 turn (90°) electric actuator - IP66

**Béné Inox** – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287  
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – [www.bene-inox.com](http://www.bene-inox.com) – [bene@bene-inox.com](mailto:bene@bene-inox.com)

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.