

Butterfly valves

Model 50636 Butterfly valve with locating holes - stainless steel body and butterfly - FKM gasket (58423) and stainless steel pneumatic actuator (50802)



Specifications

⇒ Valve

Dimensions: DN50 to DN150 (2" to 6")

Connection: with flanges PN6/PN10/
PN16/150 lbs

Operating pressure: 16 bar

Operating temperature: -10°C to +150°C

Material: CF8M stainless steel body and butterfly and FKM sleeve gasket


⇒ Pneumatic actuator

Air connection: 1/8" (VP50 to VP88) or
1/4" (VP100 to VP200)

Operating pressure: 6 to 8 bar

Operating temperature: -20°C to +85°C

Material: Stainless steel



Spring return


DN (mm)	NB (inches)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Weight (kg)	Spring return Part number
50	2"	42.5	255	210	95	8.20	450636-50SE
65	2"1/2	45.5	274	241	106	11.50	450636-65SE
80	3"	46	281	241	106	12.10	450636-80SE
100	4"	52	317	275	123	17.20	450636-100SE

Double-acting type

DN (mm)	NB (inches)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	Weight (kg)	Double-acting type Part number
50	2"	42.5	255	210	95	8.20	450636-50DE
65	2"1/2	45.5	261	210	95	8.70	450636-65DE
80	3"	46	268	210	95	9.30	450636-80DE
100	4"	52	302	241	106	13.80	450636-100DE
125	5"	55.5	323	241	106	15.30	450636-125DE
150	6"	55.5	351	275	123	22.70	450636-150DE

Béné Inox – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – www.bene-inox.com – bene@bene-inox.com

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.



N°	Part Name	Material	Quantity
1	BUTTERFLY VALVE (58423)	CF8M	1
2	FIXING BOLT	STAINLESS STEEL	4
3	WASHER	STAINLESS STEEL	4
4	ADAPTER PLATE	STAINLESS STEEL	1
5	COUPLING	STAINLESS STEEL	1
6	PNEUMATIC ACTUATOR (50802)	STAINLESS STEEL	1
7	CAPPED PNEUMATIC CONNECTOR	NICKEL-PLATED BRASS	1 (SE*) or 2 (DE**)
8	EXHAUST SILENCER	NICKEL-PLATED BRASS	1 (SE*)

*Spring return pneumatic actuator **Double-acting type pneumatic actuator

You can refer to the following product data sheets for more technical information:

- **58423:** Butterfly valve with locating holes, manual operation
- **50802:** Stainless steel pneumatic actuator

Béné Inox – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – www.bene-inox.com – bene@bene-inox.com

Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.