

Butterfly valves

Model 50730 Butterfly valve with locating holes - cast iron body - stainless steel butterfly - EPDM gasket (58459) and electric actuator IP68 with positioning unit (50846)



Specifications

⇒ Valve

Dimensions: DN40 to DN200 (1"1/2 to 8")

Connection: with flanges PN10/16

Operating pressure: 16 bar

Temperature: -30°C to +110°C

Material: Cast iron GGG50 (GJS 500-7),
CF8M and EPDM ACS sleeve gasket


⇒ Electric actuator

Operating temperature: -20°C to +70°C


Aluminium housing and plastic cap IP68

Visual position indicator

Regulated anti-condensation heater



DN40 to DN100



DN125 to DN200

Béné Inox – 11 chemin de la Pierre Blanche – 69800 SAINT-PRIEST – S.A.S with 240 000 € share capital – SIREN N° 311 810 287
Tel. N°: +33 (0)4 78 90 48 22 – Fax N°: +33 (0)4 78 90 69 59 – www.bene-inox.com – bene@bene-inox.com


Technical information, illustrations and photographs are provided for information only, they are not contractual. Some may vary according to the tolerances accepted in the profession and the applicable standards. All instructions for use, disassembly and maintenance are recommendations only. These could also vary depending on product usage conditions, its installation environment and purchaser requirements – of which the purchaser alone is responsible for their definition.

100-230V 50/60Hz and 100-350V DC

DN (mm)	NB (inches)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	Opening/ closing time (s)	Weight (kg)	Part number
40	1"1/2	33	358	192	170	X	15	6.40	450730-40A
50	2"	42.5	340	192	170	X	15	6.50	450730-50A
65	2"1/2	45.5	346	192	170	X	15	7.10	450730-65A
80	3"	46	353	192	170	X	20	8.50	450730-80A
100	4"	52	374	192	170	X	20	12.00	450730-100A
125	5"	55.5	452	209	170	275	30	16.00	450730-125A
150	6"	55.5	465	209	170	275	60	19.00	450730-150A
200	8"	60	502	209	170	275	60	24.00	450730-200A

15-30V 50/60Hz and 12-48V DC

DN (mm)	NB (inches)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	Opening/ closing time (s)	Weight (kg)	Part number
40	1"1/2	33	358	192	170	X	15	6.40	450730-40B
50	2"	42.5	340	192	170	X	15	6.50	450730-50B
65	2"1/2	45.5	346	192	170	X	15	7.10	450730-65B
80	3"	46	353	192	170	X	20	8.50	450730-80B
100	4"	52	374	192	170	X	20	12.00	450730-100B
125	5"	55.5	452	209	170	275	30	16.00	450730-125B
150	6"	55.5	465	209	170	275	60	19.00	450730-150B
200	8"	60	502	209	170	275	60	24.00	450730-200B



N°	Part Name	Material	Quantity
1	BUTTERFLY VALVE (58459)	GGG50 / CF8M	1
2	FIXING BOLT	STAINLESS STEEL	4
3	WASHER	STAINLESS STEEL	4
4	ADAPTER PLATE	STAINLESS STEEL	1
5	COUPLING	STAINLESS STEEL	1
6	ELECTRIC ACTUATOR (50846)	PLASTIC	1

You can refer to the following product data sheets for more technical information:

- **58459:** Butterfly valve with locating holes, manual operation
- **50846:** 1/4 turn (90°) electric actuator with positioning unit - IP68