



Threaded pipe fittings


ISO 7/1 (sauf NPT)
ISO 4144

20 bar à 20°C
16 bar à 100°C
**ACCESSOIRES
DE TUYAUTERIE**
Modèle **5248**

Té 3 branches femelles - Inox 316 moulé

Threaded tee (casting) - Stainless steel 316



DN (mm)	DN (pouces)	D (mm)	F (pouces)	L (mm)	Poids (kg)	Référence Gaz cylindrique	Prix unitaire	Référence NPT	Prix unitaire
6	1/8"	15	1/8"	17,5	0,04	452484-6	4,30		
8	1/4"	19	1/4"	19,5	0,05	452484-8	5,10	452485-8	5,20
10	3/8"	22	3/8"	23,5	0,07	452484-10	5,80	452485-10	6,90
15	1/2"	27	1/2"	27,5	0,12	452484-15	7,20	452485-15	8,20
20	3/4"	33	3/4"	32,5	0,17	452484-20	10,10	452485-20	12,60
25	1"	40	1"	38,5	0,26	452484-25	18,00	452485-25	17,70
32	1"1/4	49	1"1/4	45,5	0,34	452484-32	26,80	452485-32	27,90
40	1"1/2	56	1"1/2	48,5	0,43	452484-40	33,60	452485-40	32,30
50	2"	69	2"	57,5	0,67	452484-50	48,70	452485-50	50,10
65	2"1/2	86	2"1/2	69,5	1,21	452484-65	85,60		
80	3"	99	3"	78,5	2,92	452484-80	173,40		
100	4"	125	4"	96,5	4,76	452484-100	212,10		