

Threaded pipe fittings



ISO 7/1

(sauf NPT)




20 bar à 20°C

16 bar à 100°C

Modèle **5253**

Réduction mâle / femelle - Inox 316 moulé

Male / female reducer (casting) - Stainless steel 316



DN (mm)	F1 (pouces)	F2 (pouces)	L (mm)	S (mm)	Poids (kg)	Référence Gaz	Prix unitaire
10-8	3/8"	1/4"	17	18	0,01	452533-108	4,00
15-8	1/2"	1/4"	21	26	0,03	452533-158	4,40
15-10	1/2"	3/8"	21	26	0,03	452533-1510	4,60
20-8	3/4"	1/4"	24	30	0,05	452533-208	•
20-10	3/4"	3/8"	24	30	0,05	452533-2010	6,00
20-15	3/4"	1/2"	24	30	0,04	452533-2015	6,00
25-15	1"	1/2"	27	35	0,09	452533-2515	8,90
25-20	1"	3/4"	27	35	0,07	452533-2520	9,10
32-15	1"1/4	1/2"	30	45	0,20	452533-3215	12,40
32-20	1"1/4	3/4"	30	45	0,20	452533-3220	12,60
32-25	1"1/4	1"	30	45	0,20	452533-3225	12,10
40-25	1"1/2	1"	38	52	0,25	452533-4025	16,60
40-32	1"1/2	1"1/4	38	52	0,25	452533-4032	20,80
50-32	2"	1"1/4	36	63	0,34	452533-5032	24,80
50-40	2"	1"1/2	36	63	0,34	452533-5040	23,20

Filetage en Gaz conique / Taraudage en Gaz cylindrique

• Sur demande