


Single cutting ring fittings



DIN 2353

RACCORDS
À BAGUEModèle **5415****Union simple mâle - DIN 2353 - Inox 316 Ti**

Male straight union - DIN 2353 - Stainless steel 316 Ti


Filetage Gaz conique BSPT

Série	PN (bar)	D (mm)	F (pouces)	L1 (mm)	L2 (mm)	S1 (mm)	S2 (mm)	Poids (kg)	Référence BSPT	Prix unitaire
LL	100	4	1/8"	25,5	16	10	10	0,02	454153-46	•
L	315	6	1/8"	30	16	14	14	0,03	454153-66	16,60
L	315	6	1/4"	34	20	14	14	0,04	454153-68	18,60
L	315	8	1/8"	34	16	17	14	0,04	454153-86	18,50
L	315	8	1/4"	34	20	17	14	0,04	454153-88	17,00
L	315	10	1/4"	36	21	19	17	0,05	454153-108	19,90
L	315	10	3/8"	36	21	19	17	0,05	454153-1010	26,10
L	315	12	3/8"	37	22	22	19	0,06	454153-1210	23,40
L	315	12	1/2"	39	24	22	22	0,11	454153-1215	30,10
L	315	15	1/2"	40	25	27	24	0,14	454153-1515	32,00
L	315	18	1/2"	42	25,5	32	27	0,14	454153-1815	40,20

Filetage selon la norme ISO 7/1

Autres diamètres sur demande

• Sur demande


Filetage Gaz cylindrique BSPP sans joint (forme B)

Série	PN (bar)	D (mm)	F (pouces)	L1 (mm)	L2 (mm)	S1 (mm)	S2 (mm)	Poids (kg)	Référence BSPP	Prix unitaire
LL	100	4	1/8"	27	17,5	10	14	0,02	454154-46	•
L	315	6	1/8"	31	18,5	14	14	0,03	454154-66	13,20
L	315	6	1/4"	39	21	14	19	0,04	454154-68	19,50
L	315	8	1/8"	34	17,5	17	14	0,04	454154-86	16,60
L	315	8	1/4"	37	22	17	19	0,05	454154-88	13,90
L	315	10	1/4"	38	23	19	19	0,05	454154-108	16,20
L	315	10	3/8"	42,5	24,5	19	22	0,07	454154-1010	22,30
L	315	12	3/8"	39	24,5	22	22	0,07	454154-1210	24,00
L	315	12	1/2"	45	27	22	27	0,11	454154-1215	30,10
L	315	15	1/2"	43	28	27	27	0,14	454154-1515	32,90
L	315	18	1/2"	45	28,5	32	27	0,14	454154-1815	42,20
S	630	14	1/2"	51	33	27	27	0,15	454154-1415	43,50
S	400	16	1/2"	51	33	30	27	0,15	454154-1615	44,20
S	400	20	3/4"	58	36,5	36	32	0,25	454154-2020	61,20
S	400	25	1"	65	41	46	41	0,47	454154-2525	96,40
S	400	30	1"1/4	70	43,5	50	50	0,64	454154-3032	112,00
S	315	38	1"1/2	79	48	60	55	0,89	454154-3840	183,10

Filetage selon la norme ISO 228-1

Autres diamètres sur demande

• Sur demande

Filetage Gaz cylindrique BSPP avec joint FKM (forme E)

Série	PN (bar)	D (mm)	F (pouces)	L1 (mm)	L2 (mm)	S1 (mm)	S2 (mm)	Poids (kg)	Référence BSPP	Prix unitaire
LL	100	4	1/8"	27	17,5	10	14	0,02	454156-46	23,70
L	315	6	1/8"	31	18,5	14	14	0,03	454156-66	15,90
L	315	6	1/4"	39	21	14	19	0,04	454156-68	21,60
L	315	8	1/8"	34	17,5	17	14	0,04	454156-86	22,70
L	315	8	1/4"	37	22	17	19	0,05	454156-88	18,20
L	315	10	1/4"	38	23	19	19	0,05	454156-108	20,20
L	315	10	3/8"	42,5	24,5	19	22	0,07	454156-1010	30,30
L	315	12	3/8"	39	24,5	22	22	0,07	454156-1210	22,90
L	315	12	1/2"	45	27	22	27	0,11	454156-1215	34,50
L	315	15	1/2"	43	28	27	27	0,14	454156-1515	31,10
L	315	18	1/2"	45	28,5	32	27	0,14	454156-1815	40,50
S	630	14	1/2"	51	33	27	27	0,15	454156-1415	41,60
S	400	16	1/2"	51	33	30	27	0,15	454156-1615	45,10
S	400	20	3/4"	58	36,5	36	32	0,25	454156-2020	62,10
S	400	25	1"	65	41	46	41	0,47	454156-2525	97,70
S	400	30	1"1/4	70	43,5	50	50	0,64	454156-3032	135,80
S	315	38	1"1/2	79	48	60	55	0,89	454156-3840	207,00

Température de service : de -20°C à +200°C

Filetage selon la norme ISO 228-1

Autres diamètres sur demande