

Raccords à simple bague

Série
54RACCORDS
À BAGUE

Single cutting ring fittings




DIN 2353

Modèle **5424**

Union simple à souder - DIN 2353 - Inox 316 Ti

Butt welding union - DIN 2353 - Stainless steel 316 Ti



Série	PN (bar)	D1 (mm)	D2 (mm)	D3 (mm)	L1 (mm)	L2 (mm)	L3 (mm)	S1 (mm)	S2 (mm)	Poids (kg)	Référence	Prix unitaire
L	315	6	4	10	29	15	7	14	12	0,03	454242-6	19,80
L	315	8	6	12	31	15	8	17	14	0,04	454242-8	25,30
L	315	10	8	14	33	15	8	19	17	0,05	454242-10	22,30
L	315	12	10	16	33	15	8	22	19	0,06	454242-12	24,80
L	315	15	12	19	37	15	10	27	22	0,08	454242-15	28,00
L	315	18	15	22	40	16,5	10	32	27	0,14	454242-18	43,30
S	630	14	10	19	45	18	10	27	24	0,11	454242-14	44,80
S	400	16	12	21	45	18	10	30	27	0,14	454242-16	45,00
S	400	20	16	26	51	20,5	12	36	32	0,22	454242-20	61,90
S	400	25	20	31	56	24	12	46	41	0,38	454242-25	98,70
S	400	30	25	36	62	26,5	14	50	46	0,45	454242-30	121,50
S	315	38	32	44	69	31	16	60	55	0,68	454242-38	173,80

Autres diamètres sur demande